

CROSSWALK COLORS:

PANTONE # 6147 U
~SF: 935 (AS SOLID BKGND)
~SF: 320 (PAINTED AROUND
OTHER SHAPES)



PANTONE # 375 U
~SF: 390



PANTONE # 485 U
~SF: 225



GROUNDPAINT COLORS:

PANTONE # 6147 U
~SF: 6,710



PANTONE # 375 U
~SF: 160



PANTONE # 485 U
~SF: 540



PANTONE # 300 U
~SF: 3,880



PANTONE # 130 C
~SF: 480



PANTONE # 1925 C
~SF: 640



GROUND PAINT NOTES

- A. SECTION 32 18 23 – DECORATIVE ASPHALT COATING
- B. SUMMARY:
 - APPLY DECORATIVE, COLORED GROUND COATING SYSTEM ON ASPHALT PAVING USING STREETBOND 150 OR APPROVED EQUAL.
 - REFERENCES: MANUFACTURER'S CURRENT DATA SHEETS, INSTALLATION GUIDELINES, AND COLOR CHARTS.
- C. SUBMITTALS:
 - PRODUCT DATA AND SAFETY DATA SHEETS.
 - COLOR SAMPLES AND MANUFACTURER'S STANDARD COLOR RANGE.
 - PROJECT-SPECIFIC MOCK-UP APPROVAL.
- QUALITY ASSURANCE:
 - APPLICATOR SHALL BE MANUFACTURER-CERTIFIED.
 - MATERIALS SHALL BE DELIVERED IN ORIGINAL UNOPENED CONTAINERS WITH LABELS INTACT.
- MOCK-UP:
 - INSTALL MINIMUM 100 SQ. FT. SAMPLE AREA AT LOCATION DIRECTED BY LANDSCAPE ARCHITECT.
 - MOCK-UP TO DEMONSTRATE SURFACE PREPARATION, APPLICATION METHOD, TEXTURE, AND FINAL COLOR.
 - APPROVED MOCK-UP MAY REMAIN AS PART OF CONSTRUCTION.
- D. PRODUCTS:
 - MANUFACTURER:
 - STREETBOND COATINGS, A DIVISION OF GAF, OR APPROVED EQUAL.
 - PRODUCT:
 - STREETBOND 150 PAVEMENT COATING SYSTEM.
 - COLORS:
 - AS SELECTED BY LANDSCAPE ARCHITECT FROM MANUFACTURER'S FULL RANGE.
 - MATERIALS:
 - STREETBOND ADHESION PROMOTER (WHEN REQUIRED).
 - STREETBOND SEALER (IF SPECIFIED).
- E. EXECUTION:
 - EXAMINATION:
 - VERIFY ASPHALT PAVING IS FULLY CURED, STABLE, CLEAN, AND DRY PRIOR TO APPLICATION.
 - PREPARATION:
 - PREPARATION: POWER WASH AND AIR-BLAST SUBSTRATE. REMOVE GREASE, DIRT, LAITANCE, AND INCOMPATIBLE COATINGS.

